



For greater ease and reduced costs of both installation and servicing, Next Scale Stop offer an integral 3 way valve in head option in the range of POU cartridge systems. The valve has 3 positions which are easily adjusted between **Filter - Off - Bypass** modes with a single turn of the valve using the key provided.



The NSS bypass range use high performance TAC scale protection technology providing the highest level of protection against lime scale available.

The housings are manufactured in Europe to ISO 9001:2008 standards, they are NSF42 certified and comply with EU regulations for drinking water under CE 764/2008.

Next Scale Stop TAC media has an efficiency rating of > 95% under the German DVGW-W512 testing protocol (twice as efficient as electronic). Scale Stop systems have a **minimum** life in service of 12 months between cartridge changes.

The operational limit of Next Scale Stop TAC is 1300ppm CaCO₃ (hardness) Next Scale Stop TAC has the highest efficiency rating of any cartridge system currently on the market and a much longer life in service.



The Bypass range is available as:

Size	Flow rate	Model
10 inch standard	4 lpm	NSS-110
10 inch BB	8 lpm	NSS-110B
20 inch standard	8 lpm	NSS-120
20 inch BB	16 lpm	NSS-120B
Inlet/Outlet connection	3/4 to 1.25 inches	
Maximum pressure	6 Bar (90 psi)	

Next ScaleStop systems are available up to 285 litres per minute for single units.

